

AMENDMENT TO THE CLAIMS

1-21. (Cancelled)

22. (Currently Amended) A vibration damping device for damping vibrations of a machine, the vibration damping device comprising a laminated plate formed by laminating a specified number of inner plates and an outer plate that is disposed on an outside of the specified number of the inner plates, wherein intermittent welding is performed on peripheral edges of the inner plates along a circumferential direction of the inner plates when the laminated plate is coupled to a member of the machine that is an object of vibration damping and the specified number of inner plates are tightly sealed by the outer plate and the member of the machine,

~~The vibration damping device according to claim 16,~~ _____ wherein the laminated plate is formed by laminating the specified number of the inner plates, and the outer plate which is disposed on the outside of the specified number of inner plates and whose peripheral edge has a shape that partially differs from a shape defined by those of peripheral edges of the inner plates, the inner plates are caused to contact with ~~a member~~ the member of the machine that is the object of vibration damping, and the laminated plate is coupled to the member of the machine by performing continuous welding on the peripheral edge of the outer plate and performing the intermittent welding on the peripheral edges of the inner plates.

23. (Cancelled)

24. (Currently Amended) A vibration damping device for damping vibrations of a machine, the vibration damping device comprising a laminated plate formed by laminating a specified number of inner plates and an outer plate that is disposed on an outside of the specified number of the inner plates, wherein intermittent welding is performed on peripheral edges of the inner plates along a circumferential direction of the inner plates when the laminated plate is coupled to a member of the machine that is an object of vibration damping and the specified number of inner plates are tightly sealed by the outer plate and the member of the machine,

~~The vibration damping device according to claim 16,~~ wherein the member of the machine has a contact member that is capable of contacting end portions of the laminated plate, the inner plates define a contact part that protrudes from a peripheral edge of the outer plate and contacts with the contact member, and continuous welding that covers the contact part of the inner plates is performed between the peripheral edge of the outer plate and the contact member.

25. (Currently Amended) A vibration damping device for damping vibrations of a machine, the vibration damping device comprising a laminated plate formed by laminating a specified number of inner plates and an outer plate that is disposed on an outside of the specified number of the inner plates, wherein intermittent welding is performed on peripheral edges of the inner plates along a circumferential direction of the inner plates when the laminated plate is coupled to a member of the machine that is an object of vibration damping and the specified number of inner plates are tightly sealed by the outer plate and the member of the machine,

~~The vibration damping device according to claim 16,~~ _____ wherein a plurality of protruding

parts that match a peripheral edge shape of the outer plate are disposed on the peripheral edge of the inner plates, and the plurality of protruding parts of the inner plates are intermittently welded by performing continuous welding on the peripheral edge of the outer plate.

26. (Previously Presented) The vibration damping device according to claim 24, wherein a length of the contact part of the inner plates is 100 to 280 mm.

27. (Previously Presented) The vibration damping device according to claim 25, wherein the plurality of protruding parts of the inner plates are disposed at intervals of 100 to 280 mm.

28-35. (Cancelled)

36. (Previously Presented) The vibration damping device according to claim 24, wherein the contact part is demarcated by a cut-out part, and the cut-out part has a rectangular shape.

37. (Withdrawn) The vibration damping device according to claim 24, wherein the contact part is demarcated by a cut-out part, and the cut-out part has a wave shape.

38. (Previously Presented) The vibration damping device according to claim 36, wherein the cut-out part is embedded by welding and the inner plates are attached to the machine when the laminated plate is coupled to the members of the machine.

39-41. (Cancelled)